

ALP56

Approach Light PAR 56 Lamp



Model 896

COMPLIANT WITH:

FAA-E-982	Model 892
MB-2	Model 896
MIL-L-26764	Model 896
MIL-L-81015	Model 898
FAA-E-2689	
STANAG 3616	
ASCC AIR STD 65/35	
AFMAN 32-1123(I)/ TM 5-803-7	

GENERAL DESCRIPTION

All fixtures are furnished with stainless steel spring clips to hold color filter. The typical Lamps used in these fixtures are PAR56 with Mogul End Prongs.

ORDERING INFORMATION

<u>Part Number</u>	<u>Description</u>
892	Basic Fixture, No Filter or Cable (FAA-982)
894	Basic Fixture with Red Filter and 6' - 2/16GA Cable and L-823 Plug
895	Basic Fixture with No Filter and 6' - 2/16GA Cable and L-823 Plug
896	Basic Fixture with No Filter and 6' - 2/12GA Cable and L-823 Plug (Type MB-2 and MIL-L-26764)
898	Basic Fixture - Modified for PAR 64 Lamp, with Red Filter, 6' - 2/12GA Cable and L-823 Plug, (MIL-L-81015 and MS-90303)

OPTION AND RENEWALL PARTS

<u>Part Number</u>	<u>Description</u>
894 - 3R	Red Filter
894 - 3G	Green Filter
894 - 3A	Amber (Yellow) Filter
2620	Mogul Receptacle Connector - Rear Leads (No Longer Available)
N-2620	Mogul Receptacle - Side Leads (New Style)
2610	Terminal Block
9644-Q	200 Watt PAR56 Mogul end prong Lamp
9655-Q	300 Watt PAR56 Mogul end prong Lamp
9646-Q	500 Watt PAR56 Mogul end prong Lamp

TYPICAL CONFIGURATIONS AND USAGE

